

真空エジェクタバリエーション

		ZH□A							ZU□A			
シリーズ		 P.745							 P.773			
特長		接続はワンタッチとねじ込みの組合せが可能。							真空ポートと供給ポートが一直線上にあるため配管が容易。			
真空ポンプシステム												
ノズル径(mm)		0.5	0.7	1.0	1.3	1.5	1.8	2.0	0.3	0.4	0.5	0.7
最大吸込流量 [L/min(ANR)]	Sタイプ	6	12	26	40	58	76	90	1.8	3.2	7	11
	Lタイプ	13	28	52	78	78	128	155	3.4	5.8	13	16
空気消費量[L/min(ANR)]		13	27	52	88	117	165	201	4.2	7.7	14	28
適応 バッド径の目安 (mm) ※	2	●	●	●	●	●	●	●	●	●	●	●
	4	●	●	●	●	●	●	●	●	●	●	●
	6	●	●	●	●	●	●	●	●	●	●	●
	8	●	●	●	●	●	●	●	●	●	●	●
	10	●	●	●	●	●	●	●		●	●	●
	13	●	●	●	●	●	●	●			●	●
	16		●	●	●	●	●	●				●
	20		●	●	●	●	●	●				●
	25			●	●	●	●	●				
	32			●	●	●	●	●				
	40				●	●	●	●				
	50				●	●	●	●				
	63					●	●	●				
	80					●	●	●				
	100					●	●	●				
125						●	●					
150							●					
サイレンサ		●										
クランプ取付(L型/DINレール)		●										
単体・幅寸法(mm)		14~22							8.2~10.4			
単体・質量(g)		5~46.2							2.4~4.3			