

# Made to Order Common Specifications: -XB10A: Intermediate Stroke (Spacer-installed type)



## 6 Intermediate Stroke (Spacer-installed type)

Symbol  
**-XB10A**

A spacer is installed on the exclusive body (● indication). The overall length is shorter than that of the spacer-installed type 1. The ⊙ indicates the selectable stroke range. (Strokes with the ● indication are not selectable.) The — indicates strokes supported by the spacer-installed type 1.

Bore size [mm]	Stroke range	Stroke													
		55	60	65	70	75	80	85	90	95					
32 to 100	51 to 94	⊙	●	⊙	●	⊙	●	—	●	⊙	●	⊙	●	⊙	●

### Ordering example

Part no.	<b>CQ2B50-57DZ-XB10A</b>	
Description	<ul style="list-style-type: none"> <li>● Uses an exclusive tube (60 mm stroke) in "3".</li> <li>● Makes 57 mm stroke with 3 mm spacer inside.</li> <li>● The B dimension is 100.5 mm. B = 40.5 + 60</li> </ul>	


### Specifications: Same as standard type

How to Order  Q2  Standard model no.  — XB10 A

Intermediate stroke ●  
 Spacer-installed type ●

### Dimensions: CQ2 Series (Dimensions other than those below are the same as those of the standard type.)

#### Double acting, Single rod



Symbol Stroke	A												B							
	51 to 54	56 to 59	61 to 64	66 to 69	76 to 79	81 to 84	86 to 89	91 to 94	51 to 54	56 to 59	61 to 64	66 to 69	76 to 79	81 to 84	86 to 89	91 to 94				
Bore size																				
<b>32</b>	95	100	105	110	120	125	130	135	88	93	98	103	113	118	123	128				
<b>40</b>	101.5	106.5	111.5	116.5	126.5	131.5	136.5	141.5	94.5	99.5	104.5	109.5	119.5	124.5	129.5	134.5				
<b>50</b>	103.5	108.5	113.5	118.5	128.5	133.5	138.5	143.5	95.5	100.5	105.5	110.5	120.5	125.5	130.5	135.5				
<b>63</b>	109	114	119	124	134	139	144	149	101	106	111	116	126	131	136	141				
<b>80</b>	118.5	123.5	128.5	133.5	143.5	148.5	153.5	158.5	108.5	113.5	118.5	123.5	133.5	138.5	143.5	148.5				
<b>100</b>	130	135	140	145	155	160	165	170	118	123	128	133	143	148	153	158				